

HULK UNDERGROUND TREE KITS INSTALLATION

Hulk Earth Anchors are installed at the bottom of the planting hole where the tree root ball is going to be placed. The anchors are installed in a triangular pattern by driving them into the ground with a re-usable Hulk Smasher Rod. This driving process can be done with a hand held hammer or commercially available powered hammering equipment. The hammering process would generally be determined by the size of the anchor, ground conditions and the total quantity of Hulk tree anchoring kits which need to be installed.



The Hulk Earth Anchor is driven into the ground to a depth where only the D-Ring is left exposed, after which the Hulk Smasher rod is removed and the anchor is set in the ground with an upward pull on the anchor tendon. After placing the tree in the planting hole, the Hulk tensioning strap is passed through each of the anchors D-Rings and wrapped over the root ball in a triangular pattern. The strap is then tightened with the ratchet tensioner firmly anchoring the tree into position leaving only the tree above ground level.

HULK UNDERGROUND TREE KITS:

Kit Model	Tree Size	Kit Contents	Kits per Case	Weight per case
HP25UTK	For small trees up to 75mm diameter	3 X HULK HP25 Earth Anchors with fitted D-rings 1 X 2.5m green tensioning strap with ratchet	15	6kg
HP35UTK	For trees 75mm to 150mm diameter	3 X HULK HP35 Earth Anchors with fitted D-rings 1 X 5.5m blue tensioning strap with ratchet	6	15.5kg
H50UTK	For trees 150mm to 350mm diameter in hard soil	3 X HULK H50 Earth Anchors with fitted D-rings 1 X 6.5m red tensioning strap with ratchet	3	12.5kg
H80UTK	For trees 150mm to 350mm diameter in medium hard soil	3 X HULK H80 Earth Anchors with fitted D-rings 1 X 6.5m red tensioning strap with ratchet	3	14kg
H110UTK	For trees 150mm to 350mm diameter in soft soil	3 X HULK H110 Earth Anchors with fitted D-rings 1 X 6.5m red tensioning strap with ratchet	3	16.5kg
One kit anchors one tree. Hulk Smasher drive rod additional. Installation instructions included.				

For further advice and technical support visit www.hulkearthanchors.com or call 1300 692 626



Distributed By: